
Print Name

Signature

Date

1. What is the first procedure you should do to see if a truck is able to wash for a sweetener load?

2. List 5 (five) approved prior commodities

3. A _____ form must be filled out if the previous product is not on the prior commodity list.
4. Before you touch the trailer you must _____ and put on your _____ and _____ if needed, to ensure you are doing your part in proper food safety.
5. To check for product level, colorless, odorless and foreign material you need to use an _____.
6. To properly sanitize the interior of a trailer a wash of _____ for _____ is required.
7. Explain how to make "hypo" bleach solution. _____
8. What does HACCP stand for? _____
9. Name 3 contamination hazards: _____
10. Name 3 places bacteria are found: _____
11. Name five duties off of the daily/weekly sanitation schedule which pertain to the wash bays.

12. How long should parts wash/soak in the parts sink? _____
13. What type of filter is used to filter the wash water? Where is located?

14. What is the purpose of the wash water filter? _____
15. Why is it important that items that have been washed (Sanitized) do not touch the floor or grating?

16. What is the purpose of the air drier or cold water rinse? _____
17. What must you do every time you use the bathroom? _____

True & False

- 18. Aluminum hose ends, caps or fittings are approved for sweetener use. _____
- 19. Hose ends, caps, S-Pipe or other fittings are properly sprayed off on the floor. _____
- 20. To ensure that the wash has ran for 15 minutes at 180 degrees F you must check the circle chart. _____
- 21. Pre wash inspection should be done before receiving the bill of lading. _____
- 22. Maltodextrin is not an approved commodity. _____
- 23. Proper personal hygiene can prevent contamination. _____
- 24. Rings, earrings, necklaces and buttons are allowed to be worn while washing trailers. _____
- 25. You must wash hands every time you smoke before returning to work. _____
- 26. Hair and beard nets must be worn at all times while washing the interior of a trailer. _____
- 27. The parts wash sink must be drained and refilled between every wash.
(Except for systems that use the trailer effluent to wash parts) _____
- 28. A washed trailer may leave the bay prior to initialing and writing the trailer # on the circle chart. _____
- 29. Dome lid gaskets must be sprayed with a hypo solution. _____
- 30. It is permissible to go out on a trailer without a harness if it is something quick. _____
- 31. If the circle chart did not document the wash a proper time and temp it is alright to send the trailer if you know the wash was good. _____
- 32. SOP stands for ***Standard Operating Procedure***. _____